

Clow Superglas® AR Platform Step

The all new Clow Superglas® AR Step is a sturdy, durable “All Round” platform step offering safe 360° access from a strong supporting platform.

Wide integrated handrails, a wrap-around rear guardrail and gravity locking front guardrail means this step provide users with a safe and secure non-slip access platform ideal for wide range of tasks.

Insulated GRP stiles, rigid back bars, reinforced non-slip treads together with parallel steel locking stays and transport wheels make this step robust and manoeuvrable.

Available ex-stock in 3, 4, 5, 6, 7 and 8 tread sizes, these steps are supplied flat packed and complete with all required assembly tools.

Conforming with European Standard EN131 this step safely supports a maximum 150kg load.



150kg

Code	Treads	Height to Platform	Platform Dimensions	Open Height	Weight
AESAR03	3 Tread	0.86m (2'10")	0.40m x 0.58m	1.79m (5'10)	14.5kg
AESAR04	4 Tread	1.13m (3'8")	0.40m x 0.58m	2.05m (6'9")	16.1kg
AESAR05	5 Tread	1.41m (4'8")	0.40m x 0.58m	2.34m (7'8")	18.0kg
AESAR06	6 Tread	1.68m (5'6")	0.40m x 0.58m	2.63m (8'8")	20.2kg
AESAR07	7 Tread	1.97m (6'6")	0.40m x 0.58m	2.90m (9'6")	22.0kg
AESAR08	8 Tread	2.24m (7'4")	0.40m x 0.58m	3.17m (10'5")	24.0kg

Ref: LD_AESAR_180215