

Clow Alugas Dual & Triple Section Ladders

The Clow Alugas range of ladders combine high quality box section stiles with Aluminium Rungs or Treads.

The combination of high quality glassfibre stiles and aluminium rungs produces a ladder which is strong, lightweight and extremely durable.

The rectangular pultruded box section stiles are manufactured from glass reinforced plastic and are securely fitted with Clow 'D' shaped aluminium rungs.



Dual Section Alugas Ladder

Product Code	Closed Height	Extended Height	No of Rungs	Weight
AGD14	2.44m (8')	4.2m (14')	14	15.1kg
AGD18	3.05m (10')	5.49m (18')	18	18.9kg
AGD22	3.66m (12')	6.70m (22')	22	22.7kg
AGD26	4.27m (14')	7.92m (26')	26	26.5kg
AGD29	4.88m (16')	8.84m (29')	30	30.3kg
AGD33	5.49m (18')	10.06m (33')	34	34.0kg
AGD36	6.10m (20')	10.97m (36'0)	38	40.5kg

Clow Alugas Extension Ladders are built to comply with the strength requirements of EN131, ANSI14.5 and BS2037 Class 1(Rungs).

EN131: Maximum Static Vertical Load 150kg

Triple Section Alugas Ladder

Product Code	Closed Height	Extended Height	No of Rungs	Weight
AGT20	2.44m (8')	6.2m (20')	21	23.7kg
AGT27	3.05m (10')	8.2m (27')	27	29.4kg
AGT32	3.66m (12')	9.7m (32')	33	35.0kg
AGT38	4.27m (14')	11.57m (38')	39	40.7kg
AGT40	4.88m (16')	12.0m (40')	45	46.4kg