

## Clow EN131:Professional Reach-A-Light Ladder



With 5 different variations, the Clow Reach-A-Light ladder is the ultimate in versatility and is ideal for those difficult to reach jobs.

Multiple configurations include Step Ladder, an Extended Step Ladder, a Single Section Ladder, a Double Section Ladder and Triple Section Ladder.

Ideal for use in church halls, gymnasiums and any buildings with similarly high ceilings where a free standing and self supporting ladder is required.

Unique automatic rung locks prevent the ladder sections accidentally separating when the ladder is in use.

Suitable for use by the professional or DIY enthusiast.

- Easily transported
- Box-section aluminium stiles
- Automatic rung locks
- Non-slip aluminium treads
- Light weight
- Robust & durable
- EN131:Professional Standard
- Maximum load to 150kg



Clow Reach-A-Light Ladder	AECRL1	AECRL2	AECRL3	AECRL4
Number of Rungs	3 x 7	3 x 9	3 x 11	3 x 13
Maximum Ladder Length	4.40m	6.08m	7.76m	9.44m
Closed Length	2.16m	2.72m	3.28m	3.84m
Height as an "A" Frame Ladder	2.03m	2.56m	3.08m	3.61m
Height as a "Freestanding" Ladder	3.08m	4.13m	5.19m	6.24m
Stabiliser Width	0.90m	1.2m	1.35m	1.35m
Weight	13.0kg	19.0kg	24.0kg	32.5kg

Ref: LD\_AECRL\_190118