

Clow Superglas[™] EN131: Professional Insulated Platform Step

The Clow Superglas Platform Step is designed and manufactured using strong fibreglass stiles and non-slip aluminium treads.

The step's features a useful 360mm x 300mm aluminium platform, and due to their non conductive stiles are fully insulated. The steps are compliant with European Standard EN131, and are rated to support a maximum load of 150kg.



The robust, lightweight, non conductive platform step provides the perfect access solution for use within the electrical industry.

- Non-conductive Fibreglass Stiles
- Working Platform 360mm x 300mm
- Broad Aluminium Serrated Treads for a Secure Foothold



| Product Code | Treads, inc Platform | Closed Height | Open Height To Top | Open Height To Platform | Weight |
|-----------------|--|--|---|---|--|
| YGFPS02 | 2 | 1.24m | 1.11m | 0.48m | 5.7kg |
| YGFPS03 | 3 | 1.48m | 1.34m | 0.71m | 6.7kg |
| YGFPS04 | 4 | 1.74m | 1.57m | 0.94m | 8.8kg |
| YGFPS06 | 6 | 2.24m | 2.04m | 1.41m | 11.0kg |
| YGFPS08 | 8 | 2.74m | 2.83m | 1.88m | 14.6kg |
| YGFPS10 | 10 | 3.24m | 2.98m | 2.35m | 17.8kg |
| | Product Code YGFPS02 YGFPS03 YGFPS04 YGFPS06 YGFPS08 | Codeinc PlatformYGFPS022YGFPS033YGFPS044YGFPS066YGFPS088 | Product CodeTreads, inc PlatformClosed HeightYGFPS0221.24mYGFPS0331.48mYGFPS0441.74mYGFPS0662.24mYGFPS0882.74m | Product CodeTreads, inc PlatformClosed HeightOpen Height To TopYGFPS0221.24m1.11mYGFPS0331.48m1.34mYGFPS0441.74m1.57mYGFPS0662.24m2.04mYGFPS0882.74m2.83m | Product CodeTreads, inc PlatformClosed HeightOpen Height To TopOpen Height To PlatformYGFPS0221.24m1.11m0.48mYGFPS0331.48m1.34m0.71mYGFPS0441.74m1.57m0.94mYGFPS0662.24m2.04m1.41mYGFPS0882.74m2.83m1.88m |

Ref: YGFPS_EN131Professional_190108

Slip Resistant Feet