

Clow EN131:Professional Aluminium Extension Ladder

The Clow EN131:Professional Extension Ladder is an industrial ladder designed for professional use.

It's unique design features strong folding stabilisers, (instead of the awkward and unwieldy fixed stabiliser bars used by many of our competitors), an automatic rung lock, heavy duty serrated "D" shaped rungs and robust box section stiles formed from high quality 6082, T6 grade aluminium alloy.

Fully tested and compliant with the new European EN131: Professional standard this ladder supports a maximum load of 150kg.

The strong box section stiles are specially designed with a recess to protect the rung ends.

Deep 'D' shaped rungs for comfort and large angled PVC block safety feet, supported by the heavy duty folding stabilisers make this a strong and robust ladder suitable for use within a wide range of industrial environments.



Clow Dual* Section Extension Ladder to EN131:Professional

| Code | Closed Height | Extended Height | Rungs | Weight |
|----------|---------------|-----------------|--------|--------|
| AEEND2.0 | 1.92m | 3.17m | 2 x 7 | 11.5kg |
| AEEND2.5 | 2.42m | 4.17m | 2 x 9 | 13.7kg |
| AEEND3.0 | 2.92m | 5.17m | 2 x 11 | 16.0kg |
| AEEND3.5 | 3.42m | 6.17m | 2 x 13 | 17.5kg |
| AEEND4.0 | 3.92m | 7.17m | 2 x 15 | 20.1kg |
| AEEND4.5 | 4.42m | 8.17m | 2 x 17 | 26.5kg |
| AEEND5.0 | 4.92m | 8.92m | 2 x 19 | 28.8kg |
| AEEND5.5 | 5.42m | 9.92m | 2 x 21 | 33.4kg |



Clow Triple* Section Extension Ladder to EN131:Professional

| Code | Closed Height | Extended Height | Rungs | Weight |
|----------|---------------|-----------------|--------|--------|
| AEENT2.0 | 1.92m | 4.41m | 3 x 7 | 16.0kg |
| AEENT2.5 | 2.42m | 5.91m | 3 x 9 | 19.5kg |
| AEENT3.0 | 2.92m | 7.41m | 3 x 11 | 27.4kg |
| AEENT3.5 | 3.42m | 8.92m | 3 x 13 | 32.8kg |
| AEENT4.0 | 3.92m | 9.92m | 3 x 15 | 37.7kg |

Optional extras include: Wall Wheels and Balato Belting Pole Hoops.



Strong high quality aluminium box section stiles, recessed rung ends and heavy duty "D" shaped anti-slip rungs.




EN131-1:2015
EN131-2:2010
+A2:2017
EN131-3:2018
AfPS GS 2014
www.tuv.com
TM 62000958



Automatic spring loaded rung lock to prevent accidental separation of ladder sections.



Heavy duty yet lightweight rung hooks fit snugly against the ladder rungs.



Folding stabilisers lock into position to provide secure positioning and stability.

Both stabilisers can be closed for easy transportation and storage.



*Also available as single section ladders - please see website for details.

Ref: LD_AEENDENT_190503