

Clow Extra Wide Aluminium Platform Step

Key Features

Stability & Safety:

wide base, lower centre of gravity, less likely to tip or over balance...

Portability:

optimal weight, folding stays and wheels allow simple, straightforward movement and transportation...

Ease of Access:

extra wide non-slip treads, complete with full height handrails for safe and easy access...



Guardrail System:

built-in gravity guardrail and wrap around handrails to protect the operative and reduce the risk of a fall from height...

360° Working:

a large stable platform area with the ability to move around and complete tasks with ease...

Quick & Easy Setup:

save time, quick and easy to deploy, easily moved and positioned...

**European Standard EN131:Professional
Maximum Load 150kg**



Clow Extra Wide Aluminium Platform Steps with Handrails



Clow EN131:Professional AAR Platform Step

The all new Clow EN131:Professional Aluminium "All Round" platform step offers safe 360° access from a strong supporting platform.

Wide integrated handrails, a wrap-around rear guardrail and gravity locking front guardrail means this step provides users with a safe non-slip 400 x 580mm access platform suitable for a wide range of tasks.

Channel section aluminium stiles, rigid backbars, reinforced non-slip treads together with parallel steel locking stays and transport wheels make this step lightweight yet robust.

Available ex-stock in 3, 4, 5, 6, 7 and 8 tread sizes, these steps are supplied flat packed and complete with all required assembly tools.

Conforming with the new European EN131:Professional standard this step safely supports a maximum 150kg load.



Code	Treads	Height to Platform	Open Height	Closed Height	Weight
AEAAR03	3 Tread	0.846m	1.871m	2.080m	12.9kg
AEAAR04	4 Tread	1.131m	2.156m	2.380m	14.5kg
AEAAR05	5 Tread	1.391m	2.416m	2.680m	16.1kg
AEAAR06	6 Tread	1.681m	2.706m	2.980m	19.9kg
AEAAR07	7 Tread	1.961m	2.986m	3.280m	21.7kg
AEAAR08	8 Tread	2.241m	3.266m	3.580m	23.6kg

Web: www.ladders-direct.com

Email: sales@ladders-direct.com

- **Aluminium stiles**
- **Rigid reinforced back bars**
- **Extra wide non-slip aluminium treads**
- **Strong supporting access platform**
- **Wrap around integrated handrails**
- **Gravity locking guardrail**
- **360° Working**
- **Parallel steel locking stays**
- **Transport wheels**
- **Robust non-slip feet**

Clow AEAAR Aluminium All Round Extra Wide Platform Step						
Code	Treads ¹	Height to Platform	Base Width	Open Height	Closed Height	Weight
AEAAR03	3 (2 + platform)	0.846m (2'9")	0.63m (2'1")	1.871m (6'2")	2.08m (6'10")	12.9kg
AEAAR04	4 (3 + platform)	1.131m (3'8")	0.67m (2'2")	2.156m (7'1")	2.38m (7'10")	14.5kg
AEAAR05	5 (4 + platform)	1.391m (4'7")	0.70m (2'4")	2.416m (7'11")	2.68m (8'10")	16.1kg
AEAAR06	6 (5 + platform)	1.681m (5'6")	0.74m (2'5")	2.706m (8'11")	2.98m (9'9")	19.9kg
AEAAR07	7 (6 + platform)	1.961m (6'5")	0.78m (2'7")	2.986m (9'10")	3.28m (10'9")	21.7kg
AEAAR08	8 (7 + platform)	2.241m (7'4")	0.81m (2'8")	3.266m (10'9")	3.58m (11'9")	23.6kg

Note: ¹ when you count the number of treads on a step you should include the step top or top platform within the tread count.

Note: not all manufacturers treat tread counts, tread heights or platform heights the same - when you compare steps compare the overall platform height not the number of treads as some manufacturers keep tread spacing short.

Ref: AEAAR_KeyFeatures_231130.pdf

Ladders-Direct.com from the Clow Group Ltd., buy direct online @ www.ladders-direct.com

All content copyright © Ladders-Direct.com. Duplication, reproduction or direct copying of content, text or graphics without explicit permission is forbidden.