

LADDERS

-DIRECT

from
the



Clow Group

ESTABLISHED 1913



0333 800 6272

(Monday to Friday - 08:00 to 17:00)



By Appointment to
Her Majesty the Queen
Manufacturers of Access Equipment
Clow Group Ltd., Glasgow



www.ladders-direct.com



sales@ladders-direct.com

London • Midlands • Belfast • Glasgow

Class EN131 Aluminium Extension Ladders

The Aluminium Light Trade Extension Ladder is an ideal ladder designed for the needs of the commercial and light trade sectors of the building and construction industry. This ladder is also highly recommended for heavy DIY use.

The features of this ladder include strong box section stiles complete with a recess to protect the end of the rungs. With deep 'D' type rungs for comfort and safety and large angled PVC block safety feet this is a strong and stable ladder suited to a wide range of commercial trades and environments.

This ladder is only available with Push Up operation in dual, (END), and triple, (ENT), section lengths. Conforming to the European Standard classification EN131 this ladder safely supports a maximum static vertical load of 150kg.

The shorter closed lengths of the triple section ladder, together with easily separated sections, allow for easy ladder storage.



LADDERS

-DIRECT

from
the



Clow Group
ESTABLISHED 1913



0333 800 6272

(Monday to Friday - 08:00 to 17:00)



By Appointment to
Her Majesty the Queen
Manufacturers of Access Equipment
Clow Group Ltd., Glasgow

www.ladders-direct.com

sales@ladders-direct.com

London • Midlands • Belfast • Glasgow

ALUMINIUM DUAL SECTION EXTENSION LADDER TO BS EN131

Product Code	Closed Height	Extended Height	No of Rungs	Weight (kg)
END2.5	2.5m (8'2")	4.3m (14'1")	9	9.8
END3.0	3.0m (9'8")	5.3m (17'4")	11	12.1
END3.5	3.5m (11'5")	6.2m (20'3")	13	13.6
END4.0	4.0m (13'1")	7.3m (23'10")	15	16.2
END4.5	4.5m (14'8")	8.3m (27'2")	17	22.6
END5.0	5.0m (16'4")	9.0m (29'5")	19	24.9
END5.5	5.5m (18'0")	9.75m (31'10")	21	29.5

ALUMINIUM TRIPLE SECTION EXTENSION LADDER TO BS EN131

Product Code	Closed Height	Extended Height	No of Rungs	Weight (kg)
ENT2.5	2.5m (8'2")	6.0m (19'7")	9	15.6
ENT3.0	3.0m (9'8")	7.5m (24'6")	11	23.5
ENT3.5	3.5m (11'5")	9.0m (29'5")	13	28.9
ENT4.0	4.0m (13'1")	9.75m (31'10")	15	33.8

Ref:ENDENT_140708