

## Clow Light Weight Stagings BS2037 Class 1

Robustly constructed from aluminium box sections stiles with either Timber Slatted Decking infill or anti-slip ply infill to provide additional strength means that these stagings are lightweight and extremely strong.

The in-fills can be easily replaced allowing a long life, hard wearing and virtually indestructible staging.

Clow Aluminium Stagings are available in 450mm and 600mm widths and conform with British Standard BS 2037 Class 1, supporting a maximum load of 275kg.

current building regulations allowing these stagings to be used as a direct replacement for standard scaffolding boards.



Aluminium Staging with Timber Slatted Decking BS2037 Class 1

450mm Width		600mm Width	
Code	Length	Code	Length
AP8	2.4m (8')	WAP8	2.4m (8')
AP10	3.5m (10')	WAP10	3.5m (10')
AP12	3.66m (12')	WAP12	3.66m (12')
AP14	4.27m (14')	WAP14	4.27m (14')
AP16	4.88m (16')	WAP16	4.88m (16')
AP18	5.49m (18')	WAP18	5.49m (18')
AP20	6.10m (20')	WAP20	6.10m (20')
AP22	6.70m (22')	WAP22	6.70m (22')
AP24	7.32m (24')	WAP24	7.32m (24')

Aluminium Staging with Anti-Slip Decking BS2037 Class 1

450mm Width		600mm Width	
Code	Length	Code	Length
AP8WD	2.4m (8')	WAP8WD	2.4m (8')
AP10WD	3.5m (10')	WAP10WD	3.5m (10')
AP12WD	3.66m (12')	WAP12WD	3.66m (12')
AP14WD	4.27m (14')	WAP14WD	4.27m (14')
AP16WD	4.88m (16')	WAP16WD	4.88m (16')
AP18WD	5.49m (18')	WAP18WD	5.49m (18')
AP20WD	6.10m (20')	WAP20WD	6.10m (20')
AP22WD	6.70m (22')	WAP22WD	6.70m (22')
AP24WD	7.32m (24')	WAP24WD	7.32m (24')