

Manufacturers of Access Equipment

London • Midlands • Belfast • Glasgow



## Clow Single-Section Timber Ladder to BS 1129 Class 1

The Clow Single Section Ladder is a single section wooden ladder designed to meet all the basic requirements of BS 1129 Class 1 and offers a maximum load in position of use of 175kg.

The ladder's stiles are manufactured from carefully selected Doualas Fir and the wooden rungs are turned from high quality straight grained Hickory. The rungs themselves are tapered and glued into the ladder stiles to prevent moisture from adversely affecting the strength of the joint between the rungs and ladder stiles.

Available in lengths from 8' to 20', (2.43m to 6.10m), the Clow Single Section Ladder offers a straightforward and robust access solution.

This ladder is available as either an all timber construction or with wire reinforcement to provide extra strength. With a Class 1 rating this ladder will safely support a maximum load of 175kg.

If you require longer lengths than the standard 20' ladder please contact us for availability.

Single-Section Timber Ladder		
Code	Rungs	Height
WS8	8	2.43m (8'0")
W\$10	10	3.05m (10'0")
WS12	12	3.66m (12'0")
WS14	14	4.27m (14'0")
W\$16	16	4.88m (16'0")
W\$18	18	5.49m (18'0")
WS20	20	6.10m (20'0")



Ref: WS 170126