

LADDERS **-DIRECT**.com

Ladder Instructions

Before Use
Positioning & Deploying the Ladder
Using the Ladder
Repair, Maintenance and Storage

LADDERS *from the* 
-DIRECT.com Clow Group Ltd
ESTABLISHED 1913



Ladder Instructions

READ ALL INSTRUCTIONS ON AND ACCOMPANYING THE LADDER

Index

1.0 Before Use

2.0 Positioning and Deploying the Ladder

3.0 Using the Ladder

4.0 Repair, Maintenance and Storage



Ladder Instructions

1.0 Before Use

- a) Ensure that you are fit enough to use the ladder. Certain medical conditions or medication, alcohol or drugs abuse could make ladder use unsafe.
- b) When transporting ladders on roof bars or in a truck, ensure they are suitably placed to prevent damage.
- c) Inspect the ladder after delivery and before first use to confirm condition and operation of all parts.
- d) Visually check the ladder is not damaged and is safe to use at the start of each working day when the ladder is to be used.
- e) For professional users regular periodic inspection is required.
- f) Ensure the ladder is suitable for the task.
- g) Do not use a damaged ladder.
- h) Remove any contamination for the ladder such as wet paint, mud, oil or snow.
- i) Before using a ladder at work a risk assessment should be carried out respecting the legislation in the country of use.



Ladder Instructions

2.0 Positioning and Deploying the Ladder

- a) Ladders shall be deployed at the correct position, such as the correct angle for a leaning ladder, (angle of indication approximately 1:4), with the rungs or treads level.
- b) Locking devices, if fitted, shall be fully secured before use.
- c) Ladder shall be on an even, level and unmovable base.
- d) Leaning ladder should lean against a flat non-fragile surface and should be secured before use, e.g. tied or use of a suitable stability device.
- e) Ladder shall never be repositioned from above.
- f) When repositioning the ladder take into account risk of collision with the ladder e.g. From pedestrians, vehicles or doors. Secure doors (not fire exits) and windows where possible in the work area.
- g) Identify any electrical risks in the work area, such as overhead lines or other exposed electrical equipment.
- h) A ladder shall be stood on its feet, not the rungs or steps.
- i) Ladders shall not be positioned on slippery surfaces (such as ice, shiny surfaces or significantly contaminated solid surfaces) unless additional effective measures are taken to prevent the ladder slipping or ensuring contaminated surfaces are sufficiently clean.



Ladder Instructions

3.0 Using the Ladder

- a) Do not exceed the maximum total load for the type of ladder.
- b) Do not overreach; user should keep their belt buckle (navel) inside the stiles and both feet on the same step/rung throughout the task.
- c) Do not step off a leaning ladder at a higher level without additional security, such as tying off or use of a suitable stability device.
- d) Do not use standing ladders for access to another level.
- e) Do not stand on the top three steps/rungs of a leaning ladder.
- f) Do not stand on the top two steps/rungs of a standing ladder without a platform and hand/knee rail.
- g) Do not stand on the top four steps/rungs of a standing ladder with an extending ladder at the top.
- h) Ladders should only be used for light work of short duration.
- i) Use non-conductive ladders for unavoidable live electrical work.
- j) Do not use the ladder outside in adverse weather conditions, such as strong winds;
- k) Take precautions against children playing on the ladder.

continued...



Ladder Instructions

...continued

- l) Secure doors (not fire doors) and windows where possible in the work area.
- m) Face the ladder when ascending and descending.
- n) Keep a secure grip on the ladder when ascending and descending.
- o) Do not use the ladder as a bridge.
- p) Wear suitable footwear when climbing a ladder.
- q) Avoid excessive side loadings e.g. Drilling brick and concrete.
- r) Do not spend long periods of time on a ladder without regular breaks (tiredness is a risk).
- s) Leaning ladders used for access to a higher level should be extended at least 1m above the landing point.
- t) Equipment carried while using a ladder should be light and easy to handle.
- u) Avoid work that imposes a sideways load on standing ladders, such as side on drilling through solid materials (e.g. brick or concrete).
- v) maintain a handhold whilst working from a ladder or take additional safety precautions if you cannot.



Ladder Instructions

4.0 Repair, Maintenance and Storage

Repairs and maintenance shall be carried out by a competent person and be in accordance with the producer's instructions.

Ladders should be stored in accordance with the producer's instructions.

All instructions and inspection pass/fail criteria can be downloaded at www.ladders-direct.com



Ladders-Direct : Clow London Depot
Diamond Ladder Factory
562-584 Lea Bridge Road
London
E10 7DN
Tel: +44 (0) 208 558 0300
Fax. +44 (0) 0208 558 0301

Ladders-Direct : Clow Midlands Depot
Clow Business Park
Garratts Lane
Cradley Heath
B64 5AW
Tel. +44 (0) 121 559 5222
Fax. +44 (0) 121 559 0330

Ladders-Direct : Clow Belfast Depot
2/24 Limestone Road
Belfast
BT15 3AJ
Tel. +44 (0) 2890 749748
Fax. +44 (0) 2890 749758

Ladders-Direct : Clow Glasgow Depot
185 Broad Street
Glasgow
G40 2QR
Tel. +44 (0) 141 554 6272
Fax. +44 (0) 141 551 0813

sales@ladders-direct.com
www.ladders-direct.com