

## **Clow AR Platform Step**

The Clow Aluglas AR "All Round"
Platform Step is a high quality, robust
and extremely durable step offering
safe all round access from a strong
supporting platform.

Manufactured with wide non-slip treads, heavy duty handrails and a front handrail positioned 950mm above the platform deck this step offers a stable and safe access platform.

Additional safety via means of a guardrail chain or optional guardrail bar fully encloses the operative in a 360° working environment.

The combination of heavy duty glassfibre stiles, industrial strength aluminium treads and sturdy transport wheels positioned on the back stiles make this step rigid, stable and easily manoeuvrable.

With glassfibre front and back stiles this step is electrically insulated to 25,000 volts and satisfies the requirements of the American National ANSI 14.5 standard.



Clow Aluglas Ladders and Steps conform with European Standard EN131 and support a maximum static vertical load of 150kg.

Code	Treads	Weight	Height to Platform	Platform Dimensions	Overall Height
AR04	4 Tread	16.6kg	910mm	395 x 500mm	1820mm
AR05	5 Tread	18.0kg	1160mm	395 x 500mm	2120mm
AR06	6 Tread	19.4kg	1410mm	395 x 500mm	2370mm

Ref: ARPlatform\_170126

Web: www.clowgroup.co.uk

Tel: 0333 800 6272